

GENIEMAT[®] FAS

FLOORING ADHESIVE SYSTEM



PRODUCT SPECIFICATION

PRODUCT NAME: GenieMat FAS

DESCRIPTION:

GenieMat FAS is a single component 100% solids, cross-linking, polymer-based adhesive formulated for interior installation of all thicknesses of solid/engineered wood, pre-finished and unfinished wood, bamboo and dry-back wood parquet flooring. **GenieMat FAS** also has superior concrete moisture inhibition capability (becoming waterproof when fully cured) and provides isolation for cracks up to 3 mm (1/8") wide.

GenieMat FAS is solvent and isocyanate free, has negligible (0.5 g/L) VOC content, contains no hazardous chemicals as per OSHA Regulation CFR 1910.1200 and is a nonflammable, low odour adhesive that meets all requirements for indoor air quality.

This specially formulated adhesive has good early strength buildup for immediate grab and gradually builds into a tenacious but resilient bond as the chemicals in the adhesive cross-link.

APPLICATION:

GenieMat FAS is used for bonding **GenieMat** sound control underlayments to various subfloors/substrates, and for bonding specified wood finish floors to **GenieMat** sound control underlayments.

INSTALLATION METHOD:

Immediate wet set installation. 60 minute working time. Use a 45.6 kg (100 lb) roller and allow 16 hours before light traffic, 24 hours before heavy traffic and 72 hours before sanding.

BASE:

Polymer-Resin Blend

APPEARANCE:

Off white, smooth, easy-to-spread mastic

WORKING TIME:

Approximately 60 minutes, depending on temperature and humidity

SHELF LIFE:

1 year in unopened container at 21°C (70°F)

CONTACT US

For Your Project Specific Questions

Australia +61 390187696 | **Middle East** +971 4 813 5501 | **UK** +44 203 9846444

E. info@pliteq.com.au

© Pliteq Asia Pacific PTE LTD. 2021.

[®]™ Trademarks of Pliteq Inc. The information provided is accurate to the best of our knowledge at the time of issue. However, we reserve the right to make changes when necessary without further notification. Suggested application may need to be modified to conform with local building codes and conditions. We cannot accept responsibility for products that are not used, or installed, to our specifications. All listed dimensions are nominal.



www.pliteq.com.au

GENIEMAT[®] FAS

FLOORING ADHESIVE SYSTEM

PRODUCT SPECIFICATION CONTINUED

TROWEL SELECTION AND COVERAGE:

*Trowel dimension is width x depth x spacing. Coverage is approximate and may vary depending on porosity of substrate and angle at which the trowel is held. It is the installer's responsibility to apply the proper amount of adhesive for the job condition.

Installation:

All solid wood, engineered wood & bamboo, pre-finished or unfinished, all thicknesses:

Trowel Size* & Notch:

5 mm x 6.5 mm x 12.5 mm Flat V

Coverage:

5.5-6.5 m²/gal

Moisture inhibitor & wood installation one-step application:

5 mm x 6.5 mm x 12.5 mm Flat V with Spacers

3-3.5 m²/gal

Dry-back parquet:

3 mm x 3 mm x 3 mm Sq.

5.5-6.5 m²/gal

GenieMat to approved substrate:

1.5 mm x 1.5 mm x 1.5 mm Sq.

Up to 11 m²/gal

QUANTITY:

Tub: 15.1 L (4 gal)

DENSITY:

Max. 1.2 kg/L (10.2 lb/gal)

TECHNICAL DATA

PERCENT VOLATILE:

0%

VOC CONTENT:

<0.50 g/L

APPLICATION TEMPERATURE:

15 - 30°C (60 - 85°F)

APPLICATION RELATIVE HUMIDITY:

30% - 65%

FREEZE/THAW STABILITY:

Stable to -12°C (10°F)

RELATIVE HUMIDITY TEST (ASTM F2170):

Maximum 75%

Maximum 90% when used as moisture inhibited system, as per above*

CALCIUM CHLORIDE TEST (ASTM F1869):

Maximum 76 mm/93 m²/24 hrs

Maximum 254 mm/93 m²/24 hrs when used as moisture inhibited system, as per above*

*When trowel with spacers used per moisture inhibitor system above.

CONTACT US

For Your Project Specific Questions

Australia +61 390187696 | **Middle East** +971 4 813 5501 | **UK** +44 203 9846444

E. info@pliteq.com.au

© Pliteq Asia Pacific PTE LTD. 2021.

*™ Trademarks of Pliteq Inc. The information provided is accurate to the best of our knowledge at the time of issue. However, we reserve the right to make changes when necessary without further notification. Suggested application may need to be modified to conform with local building codes and conditions. We cannot accept responsibility for products that are not used, or installed, to our specifications. All listed dimensions are nominal.

